

ENS LYON**P97.32****Certificate**

Product: LOAD CELL Precision: 0.02%F.S
 Model: CZL301C-100kg Inspection Date: August02,2018
0874
 No: _____

Specifications

Rated Output	mv/v	2.9988
Non-linearity	%F.S	0.020
Hysteresis	%F.S	0.017
Repeatability	%F.S	0.017
Creep	%F.S/30min	0.017
Temp.effect on zero	%F.S/10°C	0.017
Temp.effect on span	%F.S/10°C	0.019
Zero balance	%F.S	±1
Input impedance	Ω	350±5
Output impedance	Ω	350±5
Insulation resistance	MΩ	≥5000(50VDC)
Recommended excitation voltage	VDC	9~12
Allowed excitation voltage	VDC	5~18
Compensatad temp.Range	°C	-10°C~+40°C
Operating temp.Range	°C	-20°C~+55°C
Safe overload	%F.S	120
Ultimate Overload	%F.S	150
Connection	Excitation:	<input checked="" type="checkbox"/> red:+ <input checked="" type="checkbox"/> black:- <input type="checkbox"/> yellow:-
	Signal:	<input checked="" type="checkbox"/> green:+ <input type="checkbox"/> blue:+ <input checked="" type="checkbox"/> white:-

Q.C:

Checker:

