





Dytran Instruments, Inc.

21592 Marilla St. Chatsworth, CA 91311 Ph: 818-700-7818 Fax 818-700-7880 www.dytran.com email: info@dytran.com


CALIBRATION CERTIFICATE VOLTAGE MODE ACCELEROMETER





CUSTOMER:	ALLIANTECH S	AS	TEST REPORT #: 9122						
PURCHASE ORDER #:	SALES ORDER #: 139040		PROCEDURE: TP3002						
MODEL: 3055B	1 SERIAL #:	9122	RANGE, F.S. (g's): +/- 500						
NEW UNIT X RE-CALIBRATION [1]			RECEIVED CODE	AS RETURNED CODE					
REF. SENSITIVITY (mV/g)	[2]: 9.90		TEMP (°C): 23	HUMIDITY (%): 42					
FREQUENCY RESPONSE [3]									
FREQUENCY (Hz)	SENSITIVITY (m)	V/g)	FREQUENCY (Hz)	SENSITIVITY (mV/g)					
20	10.00	×	500	9.90					
30	10.00		1000	9.90					
50	10.00		3000	9.90					
100	100 9.90		5000	9.90					
300	9.90		8000	10.10					
TRANSVERSE SENSITIVITY (%): 1.0			10000	10.20					
DISCHARGE TIME CONSTANT (sec): 0.70			BIAS VOLTAGE	(VDC): 12.3					

Amplitude Response



TEST EQUIPMENT LIST - CALIBRATION STATION # 9									
DII#	MANUFACTURER	MODEL	SERIAL#	DESCRIPTION	CAL DATE	DUE DATE			
540	BERAN INSTRUMENTS	475	182448	VIBRATION CALIBRATOR	06/06/09	06/06/10			
541	BERAN INSTRUMENTS	801A	A004	DUAL AMPLIFIER UNIT	06/06/09	06/06/10			
692	FLUKE	45	6976018	MULTIMETER	12/24/08	12/24/09			
1063	NICOLET	3091	85D02021	DIGITAL OSCILLOSCOPE	01/30/09	01/30/10			
686	DYTRAN INST.	3010M14	1684	ACCELEROMETER	10/08/09	10/08/10			

[1] AS RECEIVED / AS RETURNED CODES:

1 = IN TOLERANCE, NO ADJUSTMENTS 4 = OUT OF TOLERANCE > 5%

2 = IN TOLERANCE, NO ADJUSTMENTS 4 = 001 OF TOLERANCE > 3

2 = IN TOLERANCE, BUT ADJUSTED 5 = REPAIR REQUIRED

7 = UNIT NON-REPAIRABLE, RECOMMEND REPLACEMENT

8 = UNIT SERVICEABLE WITH CURRENT CALIBRATION DATA

3 = OUT OF TOLERANCE < 5%

6 = REPAIRED AND CALIBRATED

[2] THE REFERENCE SENSITIVITY IS MEASURED AT 100 Hz, 1G RMS.

[3] THIS CALIBRATION WAS PERFORMED IN ACCORDANCE WITH ANSI/NCSL Z540-1-1994, ISO 10012-1, ISO/IEC17025 USING THE

BACK-TO-BACK COMPARISON METHOD PER ISA RP37.2 AND IS TRACEABLE TO THE NIST THROUGH TEST REPORT # 12495-120H DUE 10-08-10

ESTIMATED UNCERTAINTY OF CALIBRATION: 2% FROM 20-100 Hz, 1.5% FROM 100-2500 Hz, 2.8% FROM 2.5KHZ-10 kHz. APPLIES TO FREQUENCY RESPONSE ONLY.

THIS CERTIFICATE SHALL NOT BE REPRODUCED EXCEPT IN FULL, WITHOUT THE WRITTEN PERMISSION FROM DYTRAN INSTRUMENTS, INC.

CALIBRATION TECHNICIAN:

PHUOC TRAN

TEST DATE:

10/23/09

RECOMMENDED RECALL DATE:

10/23/10